

Flanges type DIN 2576 PN10 with reduced thickness.

Tooling: Inner-, outer- and gasketside rolled.
Provided with three gasketgrooves.

Material: Rst. 37-2 or stainless steel.

N.B.	Outside diameter (C)	Inside diameter (D)	Thickness (E)	Number of holes (F)	Diameter of the holes (G)	Pitch circle diameter (H)	Weight (steel)
050	165	61	12	4	18	125	1,6 kg
065	185	77	12	4	18	145	2,0 kg
080	200	90	12	8	18	160	2,2 kg
100	220	116	12	8	18	180	2,4 kg
125	250	142	16	8	18	210	3,9 kg
150	285	171	16	8	22	240	4,7 kg
175	315	196	16	8	22	270	5,6 kg
200	340	222	16	8	22	295	6,1 kg
250	395	276	16	12	22	350	7,3 kg
300	445	328	16	12	22	400	8,3 kg
350	505	360	16	16	22	460	14,4 kg
400	565	411	16	16	26	515	17,1 kg
450	615	462	16	20	26	565	18,5 kg
500	670	514	16	20	26	620	21,0 kg
600	780	614	24	20	30	725	26,1 kg
700	895	716	24	24	30	840	32,7 kg
800	1015	818	24	24	33	950	41,0 kg
900	1115	920	24	28	33	1050	44,9 kg
1000	1230	1020	24	28	36	1160	53,4 kg

