

Flanges type DIN 2573 PN6 with reduced thickness.

Tooling: Inner-, outer- and gasketside rolled.
Provided with three gasketgrooves.

Material: Rst. 37-2 or stainless steel.

| N.B. | Outside diameter (C) | Inside diameter (D) | Thickness (E) | Number of holes (F) | Diameter of the holes (G) | Pitch circle diameter (H) | Weight (steel) |
|------|----------------------|---------------------|---------------|---------------------|---------------------------|---------------------------|----------------|
| 050 | 140 | 61 | 12 | 4 | 14 | 110 | 1,1 kg |
| 065 | 160 | 77 | 12 | 4 | 14 | 130 | 1,4 kg |
| 080 | 190 | 90 | 12 | 4 | 18 | 150 | 2,0 kg |
| 100 | 210 | 116 | 12 | 4 | 18 | 170 | 2,2 kg |
| 125 | 240 | 142 | 16 | 8 | 18 | 200 | 3,4 kg |
| 150 | 265 | 171 | 16 | 8 | 18 | 225 | 3,8 kg |
| 175 | 295 | 195 | 16 | 8 | 18 | 255 | 4,5 kg |
| 200 | 320 | 222 | 16 | 8 | 18 | 280 | 5,0 kg |
| 250 | 375 | 276 | 16 | 12 | 18 | 335 | 5,9 kg |
| 300 | 440 | 327 | 16 | 12 | 22 | 395 | 7,9 kg |
| 350 | 490 | 360 | 16 | 12 | 22 | 445 | 10,3 kg |
| 400 | 540 | 411 | 16 | 16 | 22 | 495 | 11,3 kg |
| 450 | 595 | 461 | 16 | 16 | 22 | 550 | 13,1 kg |
| 500 | 645 | 512 | 16 | 20 | 22 | 600 | 14,1 kg |
| 600 | 755 | 614 | 24 | 20 | 26 | 705 | 22,0 kg |
| 700 | 860 | 716 | 24 | 24 | 26 | 810 | 25,8 kg |
| 800 | 975 | 818 | 24 | 24 | 30 | 920 | 31,8 kg |
| 900 | 1075 | 920 | 24 | 24 | 30 | 1020 | 35,2 kg |
| 1000 | 1175 | 1022 | 24 | 28 | 30 | 1120 | 38,1 kg |

